



SPECIFICATIONS:

1. VOLTAGE/CURRENT RATING: 30V/0.3A AC;
2. WITHSTANDING VOLTAGE: 100V AC ONE MINUTE;
3. INSULATION RESISTANCE: 50MΩ MIN;
4. CONTACT RESISTANCE: 100mΩ MAX;
5. OPERATING TEMPERATURE RANGE: -35° C TO 85° C.

MATERIAL:

1. INSULATOR: LCP UL 94V-0 BLACK;
2. TERMINAL: COPPER ALLOY;
3. METAL FITTINGS: COPPER ALLOY.

PLATING:

1. TERMINAL: GOLD PLATING,
NICKEL 50u" MIN. OVER ALL;
2. METAL FITTINGS: TIN 100u" MIN. OVER NICKEL 50u"MIN.

PIN NO.	A	B	C
10	3.80	3.20	1.60
12	4.20	3.60	2.00
14	4.60	4.00	2.40
16	5.00	4.40	2.80
20	5.80	5.20	3.60
24	6.60	6.00	4.40
30	7.80	7.20	5.60
34	8.60	8.00	6.40
40	9.80	9.20	7.60

X,±	X°,±	UNITS mm	NAME<INTENDED USE>	东莞市铭标电子科技有限公司
.X± 0.05	.X°± 1°	MAT'L	PART NO.<INTENDED USE>	
.XX± 0.02	.XX°± 0.5°	N/A	FINISH	DWG NO.:
.XXX± 0.015	.XXX°±	N/A	APPD:	MIB-018MXXX
THE GENERATED DRAWING IS BY ACAD, PROE OR IDEAS.DO NOT CHANGE BY HAND.			Q'TY	CHKD:
			N/A	DR:
				SCALE SHEET REV.
				1:1 1/1 A