



进胶点，不许高出胶芯面



MIB-011M002



Recommended PCB layout

备注:

1. 塑胶材质: LCP UL 94V-0 BLACK;
2. 毛边最大0.03mm, 厚0.05mm;
3. 产品不可有明显的缩水, 烧焦, 发白, 缺胶, 端子包胶等问题;
4. 零件必须符合RoHS要求;
5. ▼符号为QIP管控尺寸;
6. 模穴号 (A, B, C.....);
7. 中转收料10K PCS/盘;
8. 产品几何中心位置不能设项出位;
9. 端子接地片共面度在0.05mm以内, 正位度0.02mm以内;
10. 进胶口采用底部细水口进胶;

X,±	X°,±	UNITS mm	NAME<INTENDED USE>	东莞市铭标电子科技有限公司
.X± 0.05	.X°± 1°	MAT'L	PART NO.<INTENDED USE>	
.XX± 0.02	.XX°± 0.5°	N/A	APPD:	TITLE: 成品
.XXX± 0.015	.XXX°±	FINISH N/A	Q'TY	DWG NO: MIB-011M002
THE GENERATED DRAWING IS BY ACAD, PROE OR IDEAS.DO NOT CHANGE BY HAND.			CHKD:	
			DR:	
				SCALE
				SHEET
				REV.
				1:1
				1/1
				B