



	1	2	3	4	5	6	7	8	9	10
A										
B										
C										
D										
本公司智慧财产未经许可不得复制 ming biao copyright may not be used without permission from ming biao.										

E	SPECIFICATIONS: Operating temperature range: -25℃to+75℃ Rating:30V DC, 30mA Insulation resistance:100MΩ min.100V DC Dielectric strength:250V.AC.1Min Contact resistance:50mΩ Max Life:100, 000 Cycles Travel:0.25±0.1mm Operating force:160±50gf									
F	 P.C.B LAYOUT									
G	灯光	灯光代码								
	白光	W white								
	红光	R Red								
	绿光	G Green								
	黄光	Y Yellow								
	蓝光	BL Blue								
H	..									

MING BIAO 铭标				2024.06.22				ISSUED			
R&D DEPT											

TOLERANCE				DESIGN		DATE		TITLE	
UNLESS OTHERWISE STATED				WYJ		2024. 06. 22		Illuminated Switch	
XX	±0.20	SIZE	A4	CHKD	DATE		MODEL	LSP643-084J-R	
XXX	±0.15	REV	A	DATE					
X.XXX	±0.10	UNIT	mm	APPD	DATE		SHEET	1/3	
△	±2°	SCALE	4:1	DATE		PRINT DATE		2025.02.11	

G	东莞市铭标电子科技有限公司 Ming Biao Electronic Technology Co., Ltd.									
H										

RoHS COMPLIANT Pb Pb-free Hf Hexavalent Free  东莞市铭标电子科技有限公司 Ming Biao Electronic Technology Co., Ltd.				G			
TOLERANCE				DESIGN			
UNLESS OTHERWISE STATED				DATE	TITLE		
X.X	±0.20	SIZE	A4	%yy% 2024. 06. 22	Illuminated Switch		
X.XX	±0.15	REV	A	DATE	MODEL		
X.XXX	±0.10	UNIT	mm	DATE	LSP643-084J-R		
∠	±2°	SCALE	4:1	APPD	SHEET		
				PRINT DATE	1/3		
							
H							