






本公司智慧财产未经许可不得复制
ming biao copyright may not be used without permission from ming biao.



SPECIFICATIONS:
1. CONTACT RESISTANCE: 20mΩ (Max)
2. INSULATION RESISTANCE:
100VDC-100MΩ (Min)
3. DIELECTRIC STRENGTH: 1500VAC-1MINUTE.
4. MECHANICAL LIFE CYCLE: 100,000 CYCLES.
5. OPERATING TEMPERATURE: -40 TO +85°C.
6. FRONT SEAL: IP 68.
RATING
1. RESISTIVE LOAD: 10A 125/250VAC, 15A 28VDC.
2. INDUCTIVE LOAD: 15A 28VDC.

Model	Switching Position			Schematic
	1 2 3 COM.	1 2 3 COM.	1 2 3 COM.	
SG1	ON	NONE	ON	
SG2	OFF	NONE	(ON)	
SG3	ON	OFF	ON	
SG4	(ON)	OFF	(ON)	
SG5	(ON)	OFF	ON	
SG9	OFF	NA	ON	
Term. Comm.	2-1	OPEN	2-3	

NO.	PART NAME	MATERIAL	Q'TY	FINISHING
1	ACTUATOR	COPPER ALLOY	1	Cr PLATED
2	HOUSING	NYLON (UL94V-0)	1	
3	BUSHING	ZINC ALLOY	1	
4	TERMINAL	COPPER ALLOY	3	Ag PLATED
5	CONTACT	COPPER ALLOY	1	Ag PLATED
6	D-RING	SILICONE RUBBER	1	
7	SHEEL	STAINLESS STEEL	1	Ni PLATED



TOLERANCE				DESIGN			
UNLESS OTHERWISE STATED				DATE			
XX	±0.20	SIZE	A4	TITLE			
XXX	±0.15	REV	A	Toggle Switches			
XXX	±0.10	UNIT	mm	MODEL			
				HT-SG4B3T1T23			
				DATE			
				2024.09.18			
				SHEET			
				1/2			
				PRINT DATE			
				2025.02.11			

东莞市铭标电子科技有限公司
Ming Biao Electronic Technology Co., Ltd.